


GPS Module for DriveRight®600E and CarChip® Fleet Pro



8128

The optional GPS module records the vehicle's location, GPS speed, and direction of travel at intervals between 1 second and 10 minutes when connected to either a DriveRight 600E or CarChip Fleet Pro via the GPS/Wireless Interface Module for DriveRight (# 8127) or the GPS/Wireless Interface Module for CarChip (# 8251).

If connected to a DriveRight device, the DriveRight 600E LCD displays the current latitude and longitude, the direction of travel, and the vehicle's GPS speed. The GPS data can be viewed and organized in the DriveRight Fleet Management Software (FMS, # 8186) and exported to mapping software (such as Microsoft MapPoint®) to show the exact route of each trip. Each GPS record includes speed, direction, and the status of the DriveRight 600E's two digital inputs, which can be used to provide a comprehensive profile of operation of vehicle accessories such as brakes or headlights during the course of a trip.

Note: The GPS module is optional for the DriveRight 600E and cannot be used with previous versions of the DriveRight device. The GPS Module must be enabled in the DriveRight device prior to installation via FMS for the module to function. You must have FMS version 3.0 or later to configure the GPS module for operation.

If connected to CarChip Fleet Pro, the GPS data can be displayed in two ways.

With a CarChip Connect service plan, the data can be uploaded to your CarChipConnect.com home page. Each GPS breadcrumb will be shown as flags along the trip route on the map, with speed and heading.

Or, data can be displayed on your PC via the DriveRight Fleet Management Software (FMS, # 8186). The GPS data can be viewed and organized in FMS and exported to mapping software (such as Microsoft MapPoint®) to show the exact route of each trip. Each GPS record includes speed and direction.

Note: The GPS/Wireless Interface Module for DriveRight (# 8127) or the GPS/Wireless Interface for CarChip (# 8251) must be installed in conjunction with the GPS Module.

General

Operating Temperature	-40°F to +176°F (-40°C to +80°C)
Storage Temperature	-40°F to +194°F (-40°C to +90°C)
Input Power	5 Vdc
Memory Backup	Lithium cell, estimated 5 year service life
Typical Operating Current	60mA
Typical Standby Current	0mA (module is turned off when logout interval has elapsed.)
Frequency	1575.42 MHz (L1)
Size (l x w x h)	2.00" x 1.60" x 0.50" (51 mm x 41 mm x 13 mm)
Weight	2.88 oz. (0.08 kg)
Cable	
Length	78" (2 m)
Connector	6-pin locking Mini-DIN

GPS Module for CarChip Fleet Pro and DriveRight 600E**GPS Module Receiver Specifications**

Frequency	1575.42 MHz (L1)
Number of Channels	20
Position Accuracy	<3 m
Sensitivity	-159 dBm (typical)
Velocity Accuracy	0.22 mph (0.10 m/s) typical
Dynamic Limits	
Acceleration	4g max
Jerk	4 m/s ³
Startup Time To First Location Fix	
DriveRight unplugged for:	
0 - 5 minutes	15 seconds
More than 5 minutes	35 seconds
Update interval	<1.0 seconds
Re-Acquisition Time, (after 60 second)	10 seconds

Package Dimensions

Product #	Package Dimensions (Length x Width x Height)	Package Weight	UPC Codes
8128	6.25" x 4.25" x 2.13" (159 x 108 x 54 mm)	4.8 oz. (.14 kg)	011698 00870 4