



The Vantage Connect Retrofit Kit (# 6626) converts an existing Vantage Pro2™ or Vantage Vue® console or Wireless Weather Envoy™ into a Vantage Connect cellular modem that transmits data from the console to WeatherLink.com. Data can then be downloaded to any computer. The data update interval is based on the purchased data plan. The Vantage Connect Retrofit Kit receives the data stored in the serial Weatherlink® data logger (6510SER) and sends it via cellular connection to your secure page on www.weatherlink.com

An annual data service plan is required. Select 5-minute, 15-minute, or 60-minute update plans based on different countries. WeatherLink for Windows, serial (6510SER) is required.

General

| | |
|---|---|
| Cellular Bands | 850, 900, 1800, 1900 MHz |
| Operating Temperature. | -22° to +149°F (-30° to +65°C) |
| Storage Temperature | -40° to +185°F (-40° to +85°C) |
| Current Draw. | 25mA typical, GPRS class 10: 146mA typical |
| Transmitter Power. | 2W @ 850/900 MHz (Class 4) 1W @ 1800/1900 MHz (Class 1) |
| AC Power Adapter. | 12 VDC, 1.5A peak power 2.1mm barrel jack |
| Housing Material | Rugged ABS Plastic |
| Dimensions (width x length x height). | 2.6 " x 3.75" x 1.2" (66mm x 95.25mm x 30.84mm) |
| Weight | 0.28 lb (127 g) |

Certifications

- FCC
- PTCRB
- CE
- Carrier

Package Dimensions

| Product # | Package Dimensions (Length x Width x Height) | Package Weight | UPC Codes |
|-----------|--|-------------------|--------------|
| 6626 | 10.125" x 5.625" x 2.75" (257.2 mm x 142.9 mm x 69.9 mm) | 1.28 lbs. (581 g) | 011698009534 |
| 6626EU | | 1.38 lbs. (626 g) | 011698009565 |
| 6626UK | | 1.54 lbs. (699 g) | 011698009572 |